



Technical specification

- ✓ Approval : 2014/68/EU (Pressure Equipment Directive)
- ✓ Standard : ISO 9809-2
- ✓ Material : Steel - CrMo
- ✓ Connection : M18 x 1.5 neck thread
- ✓ Service life : Unlimited
- ✓ Working pressure : 300 bar
- ✓ Test pressure : 450 bar
- ✓ Breathing gas : Breathing air (EN10012)
- ✓ Volume : 12.0 L (2 x 6.0 L)
- ✓ Length : 636 mm
- ✓ Width : 331 mm
- ✓ Thickness : 147 mm
- ✓ Weight : 21.0 kg (empty)

Product description

The low profile of the Divator steel pack configuration allows the diver to work with less water resistance in fast-flowing currents. With the cylinder valve facing downward there are no valves or hoses behind the diver's head, greatly reducing snagging hazards. The valve down configuration allows the diver to reach the valve and all hoses even when wearing a restricting dry suit. The handle makes it is to carry the cylinder pack and also acts as protection for the regulator.

- Low profile gives safer access to confined spaces
- Low profile minimizes resistance in current waters
- Excellent balance for the diver
- Quick connection interface to harness or BC/BCW
- Convenient carrying handle
- Regulator position simplifies cylinder valve handling